# BINOPTIC electronic tap

Ref. 379ENC

Mains supply

## DESCRIPTION

**BINOPTIC electronic tap - Ref. 379ENC**

Recessed electronic basin tap:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Filter and solenoid valve M3/8".
Chrome-plated brass body.
Chrome-plated spout for recessed installation.
Anti-blocking security.
Spout with smooth interior and low volume of water (limits bacterial niches).
Suitable for people with reduced mobility.
30-year warranty.

## ADVANTAGES

- Total hygiene: no manual contact
- 90% water savings
- Independent IP65 electronic control unit
- Anti-bacterial proliferation duty flush

## TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 379ENC**

| | |
|---|---|
| Supply | 230/12V mains supply |
| Connector | M3/8" |
| Technology | Electronic |
| Spout length | 200mm |
| Flow rate | 3 lpm |
| Norms | ACS CE |
| Warranty | 30 YEAR WARRANTY |