

## TEMPOMIX time flow mixer

Ref. 795209






### DESCRIPTION

TEMPOMIX time flow mixer - Ref. 795209

Cross wall single control time flow basin mixer:  
Soft-touch operation.  
Temperature control and operation via the push-button.  
Time flow ~7 seconds.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant flow straightener.  
Chrome-plated solid brass body M $\frac{3}{4}$ ".  
Filters and non-return valves.  
Adjustable maximum temperature limiter.  
Tamperproof cross wall control  $\leq 220$ mm.  
Tamperproof fixed cross wall spout  $\leq 230$ mm.  
System for fixing to the wall via anti-rotating pin, back-nut and connection clamp.  
Threaded rods can be cut-to-size.  
Chrome-plated metal control.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMIX time flow mixer - Ref. 795209

Connector	M $\frac{3}{4}$ "
Technology	Time flow
Length	230mm
Spout length	75mm
Flow rate	3 lpm
Norms	ACS  
Warranty	

### ADVANTAGES



Exceptional water savings: 85%



Soft-touch operation



Solid brass, installation behind partition



Temperature selection

