

TEMPOFLUX 2 direct flush valve

Ref. 762150

Direct flush WC valve






DESCRIPTION

TEMPOFLUX 2 direct flush valve - Ref. 762150

Flush system without cistern: directly connected to pipework.
 For walls $\leq 140\text{mm}$.
 3L/6L dual flush can be adjusted to 2L/4L.
 Soft-touch operation.
 Vacuum breaker.
 Integrated stopcock and flow rate / flush volume adjuster.
 Solid brass body.
 Chrome-plated metal push-button.
 In-line inlet $M\frac{3}{4}"$.
 Outlet connection for PVC tube $\varnothing 26/32\text{mm}$.
 Threaded rod can be cut to size.
 Acoustic level complies with European standard EN 12541 class II.
 Upstream supply pipes: minimum $\varnothing 20\text{mm}$ required at all points (including connectors).
 Base flow rate: 1 L/sec at 1 bar dynamic pressure.
 Compatible with rain water.
 Suitable for rimless WC pans without flow rate regulation.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 direct flush valve - Ref. 762150

Connector	$\frac{3}{4}"$
Technology	Time flow
Length	140mm
Flow rate	3L/6L
Norms	 
Warranty	

ADVANTAGES



Soft-touch operation



Dual flush 3L/6L



No cistern: no stagnant water



Cross wall installation

