TEMPOMATIC 3 electronic tap

Ref. 44200615

Integrated batteries, Ø 15mm stopcock



DESCRIPTION

TEMPOMATIC 3 electronic tap - Ref. 44200615

Deck-mounted electronic basin tap:

Battery-operated with integrated 223 CR-P2 6V Lithium batteries.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated solid brass body.

Cap fixed in place by two concealed screws, with pictogram to easily identify sensor.

PEX flexible Ø 15mm for compression fittings with stopcock and filter.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

ADVANIAGES



Batteries integrated in mixer body



90% water savings



Total hygiene: no manual contact




Duty flush limits bacterial proliferation

TECHNICAL CHARACTERISTICS

TEMPOMATIC 3 electronic tap - Ref. 44200615

Supply	6V battery
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	100mm
Spout length	120mm
Flow rate	3 lpm
Norms	JWRAS
Warranty	30 B WARRANTY



© DELABIE https://www.delabie.co.uk