

TEMPOFLUX time flow urinal valve

Ref. 778756

Time flow 3 seconds. For DELABIE DELTACÉRAM urinals.




DESCRIPTION

TEMPOFLUX time flow urinal valve - Ref. 778756

Exposed time flow urinal valve:
For DELABIE DELTACÉRAM urinals.
Wall-mounted exposed installation.
Soft-touch operation.
Time flow pre-set at ~3 seconds.
Flow rate pre-set at 0.15 L/sec. at 3 bar, can be adjusted up to 0.3 L/sec.
Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).
Compatible with rain water.
Complies with European standard EN 12541 (class II acoustic level).
Chrome-plated solid brass body M $\frac{1}{2}$ ".
With chrome-plated neck tube.
Angled for recessed inlet.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOFLUX time flow urinal valve - Ref. 778756

Connector	$\frac{1}{2}$ "
Technology	Time flow
Height	313mm
Flow rate	0.15 L/sec
Warranty	

ADVANTAGES



Eco time flow 3 seconds



Soft-touch operation



Stopcock built-in to wall plate



Sleek design

