

TEMPOMATIC urinal valve

Ref. 428206

Electronic, battery-operated




DESCRIPTION

TEMPOMATIC urinal valve - Ref. 428206

Cross wall electronic urinal valve:
CR123 6V lithium battery-operated, electronic control unit with solenoid valve, filter and stopcock M $\frac{1}{2}$ ".
Cross wall installation \leq 225 mm.
Shock-resistant infrared presence detection sensor.
Detection distance, time flow and flow rate can be adjusted during installation.
Detection delay is 3 seconds.
Automatic pre-rinse is possible.
Time flow ~3 seconds, can be adjusted from 3 - 12 seconds.
Hygienic duty flush every 24 hours after last use: prevents vacuums.
Flow rate 0.3 L/sec. at 3 bar, can be adjusted.
Wall plate flush to the wall.
Threaded rod can be cut to size.
Compatible with rain water.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC urinal valve - Ref. 428206

Supply	6V batteries
Connector	1/2"
Technology	Electronic
Length	225mm
Flow rate	0,3 l/sec
Warranty	

ADVANTAGES



Total hygiene: no manual contact



ECO time flow 3 seconds



Cross wall installation



Hygienic duty flush

