

TEMPOFLUX time flow urinal valve

Ref. 778765

Time flow 7 seconds. For standard urinal Ø 35mm. In-line tube




DESCRIPTION

TEMPOFLUX time flow urinal valve - Ref. 778765

Exposed time flow urinal valve:
For standard or siphon action urinals.
Wall-mounted exposed installation.
Soft-touch operation.
Time flow pre-set at ~7 seconds.
Vacuum breaker.
Flow rate pre-set at 0.15 L/sec. at 3 bar, can be adjusted up to 0.3 L/sec.
Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).
Compatible with rain water.
Complies with European standard EN 12541 (class II acoustic level).
Chrome-plated solid brass body M½".
30mm in-line chrome-plated tube and connection washer Ø 35mm.
Angled for recessed inlet.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOFLUX time flow urinal valve - Ref. 778765

Connector	½"
Technology	Time flow
Height	320mm
Flow rate	0.15 L/sec
Width to the wall	50mm
Warranty	

ADVANTAGES



Time flow 7 seconds



Soft-touch operation



Stopcock built-in to wall plate



Sleek design

