

SPORTING 2 shower panel

Ref. 714800

Electronic mains supply, scale-resistant nozzle




DESCRIPTION

SPORTING 2 shower panel - Ref. 714800

Electronic shower panel:
Anodised aluminium and chrome-plated satin finish panel.
Adjustable connector for top or back inlets.
Slimline structure with concealed fixings.
Mains supply 230/6V.
Infrared presence detection. Shower starts when hand is moved towards the sensor (detection distance ~4cm).
Shuts off voluntarily or automatically after ~60 seconds.
Duty flush (~60 seconds every 24 hours after the last use).
Flow rate 6 lpm at 3 bar.
Tamperproof, scale-resistant fixed shower head with automatic flow rate regulation.
Adjustable spray.
Accessible filter.
Integrated stopcock.
M½" connection for mixed water supply.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

SPORTING 2 shower panel - Ref. 714800

Supply	Mains supply 230/6V
Connector	M½"
Technology	Electronic
Height	1015mm
Depth	21mm
Width	70mm
Flow rate	6 lpm
Finish	Aluminium
Norms	ACS  
Warranty	



ADVANTAGES



Total hygiene: no manual contact



Anti-bacterial proliferation duty flush



80% water savings



Accessible stopcock and filter

