

# TEMPOFLUX 1 direct flush valve

Ref. 761110

Time flow direct flush WC valve





## DESCRIPTION

TEMPOFLUX 1 direct flush valve - Ref. 761110

Time flow direct flush valve for cross wall installation:  
 For walls  $\leq 200\text{mm}$ .  
 Soft-touch operation.  
 Time flow  $\sim 7$  seconds.  
 Vacuum breaker.  
 Stopcock and flow rate/volume adjuster are integrated.  
 Chrome plated metal body.  
 Inline inlet  $M\frac{3}{4}"$ .  
 Connection washer  $\varnothing 32/55\text{mm}$ .  
 Threaded rod can be cut to size.  
 Upstream supply pipes: minimum  $\varnothing 20\text{mm}$  required at all points (including connectors).  
 Base flow rate: 1 l/sec at 1 bar dynamic pressure.  
 Compatible with rain water.  
 Suitable for people with reduced mobility.  
 30-year warranty.  
 [Formerly ref: 761200]

## TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush valve - Ref. 761110

Connector	$\frac{3}{4}"$
Technology	Time flow
Length	200mm
Norms	
Warranty	

## ADVANTAGES



No cistern: no stagnant water



Cross wall installation



Powerful flush is immediately available



Direct flush reduces the risk of leaks

