

SECURITHERM electronic shower kit

Ref. 792459

Thermostatic electronic, kit 2/2



DESCRIPTION

SECURITHERM electronic shower kit - Ref. 792459

Recessed thermostatic electronic shower, kit 2/2:
 Tamperproof polished satin stainless steel control plate 195 x 220mm.
 SECURITHERM thermostatic shower mixer ¾".
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Adjustable temperature from 32° to 40°C, pre-set at 38°C.
 Battery-operated with CR-P2 223 6V Lithium battery.
 Infrared presence detection. Shower starts when hand is 4cm from the sensor.
 Shuts off voluntarily or automatically after ~60 seconds.
 Duty flush (~60 seconds every 24 hours after the last use).
 Flow rate set at 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 Concealed fixings, M½" stopcocks.
 Integrated non-return valves and filters.
 Chrome-plated Bayblend® control knob.
 Electronic shower kit suitable for people with reduced mobility.
 30-year warranty.
 Order with recessed waterproof housing ref. 792BOX.

ADVANTAGES



Total hygiene: operate without manual contact



Automatic anti-bacterial duty flush






Thermostatic temperature control



Instant shut-off if cold water fails

TECHNICAL CHARACTERISTICS

SECURITHERM electronic shower kit - Ref. 792459

| | |
|------------|---|
| Supply | 6V batteries |
| Connector | ½" |
| Technology | Electronic |
| Height | 195mm |
| Depth | 110mm |
| Width | 220mm |
| Flow rate | 6 lpm |
| Finish | Satin finish stainless steel |
| Norms | ACS   |
| Warranty |  |

