

TEMPOMATIC 4 electronic tap

Ref. 44000615CO

Integrated batteries, stopcock Ø 15mm



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 44000615CO

Deck-mounted electronic basin tap:
 Battery-operated with integrated CR123 6V Lithium batteries.
 Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated stainless steel body.
 Cap fixed in place by two concealed screws.
 Copper tails with stopcock, filter and Ø 15mm conical inlet.
 Fixing reinforced by two stainless steel rods.
 Anti-blocking security.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 44000615CO

Supply	6V batteries
Connector	M½" Ø 15mm
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Warranty	

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Batteries integrated in tap body



Anti-bacterial proliferation duty flush

