

## BINOPTIC 2 electronic tap

Ref. 37403015

Mains, deck-mounted, stopcock, H. 170mm



### DESCRIPTION

#### BINOPTIC 2 electronic tap - Ref. 37403015

Deck-mounted chrome-plated matte black electronic basin tap:  
230/6V mains supply.  
Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant aerator.  
Adjustable duty flush (~60 seconds every 24 hours after the last use).  
Stainless steel tap, 170mm high for semi-recessed basins.  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
PEX flexible with stopcock, filter and Ø 15mm conical inlet.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Smooth interior spout with low water volume (limits bacterial niches).  
Set duty flush and launch thermal shocks manually.  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

#### BINOPTIC 2 electronic tap - Ref. 37403015

Supply	230/6V mains supply
Connector	M½" Ø 15mm
Technology	Electronic
Drop height	170mm
Flow rate	3 lpm
Finish	Chrome-plated matte black
Warranty	

### ADVANTAGES



Total hygiene: no manual contact



90% water savings



Anti-bacterial proliferation duty flush



Sleek design

