

Shower kit with thermostatic mixer

Ref. H9630KIT

Riser kit with thermostatic mixer with no non-return valves

2024 UK public price excluding VAT: £477.03

DESCRIPTION

Shower kit with thermostatic mixer - Ref. H9630KIT



Shower riser kit with thermostatic sequential mixer.
Shower riser rail with SECURITHERM thermostatic shower mixer.
Thermostatic sequential mixer: opens and closes with cold water.
Mixer with no non-return valves on the inlets (reduces bacterial proliferation).
No risk of cross flow between hot and cold water.
Sequential mixer with anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant, thermostatic sequential cartridge:
Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.
Thermal shocks are possible.
Body with smooth interior and low water volume.
Flow rate regulated at 9 lpm.
Chrome plated brass body and Hygiene lever L. 100mm.
M1/2" bottom shower outlet.
Wall-mounted mixer with offset STOP/CHECK connectors, M1/2" M3/4".
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics

- Sliding shower head holder (ref. 813) on a chrome-plated riser rail (ref. 821) with soap dish and flexible shower hose (ref. 836T1).
- Shower head retaining collar (ref. 830).

Suitable for people with reduced mobility.
30-year warranty.





TECHNICAL CHARACTERISTICS


Shower kit with thermostatic mixer - Ref. H9630KIT

Connector	M1/2"
Technology	SECURITHERM single control, Securitouch
Depth	185mm
Length	184mm
Flow rate	9 lpm
Temperature limiter	39°C
Finish	Chrome-plated brass
Norms	ACS 
Warranty	



ADVANTAGES

-  Sequential: opens/closes with cold water
-  Maximum hygiene: no non-return valves
-  SECURITHERM: optimal anti-scalding safety
-  Thermostatic: complete temperature stability



Repairability

