TEMPOMATIC shower panel

Ref. 452300

Electronic

2024 UK public price excluding VAT: £756.49



ADVANTAGES



Total hygiene: operate without manual contact



Automatic flush anti-bacterial proliferation

DESCRIPTION

TEMPOMATIC shower panel - Ref. 452300

Electronic shower panel:

Anodised aluminium shower panel for wall-mounted, exposed installation. With top inlet via in-line stopcock, M1/2".

TEMPOMATIC electronic mixer for mixed water supply.

Battery-operated with 223 6V Lithium battery.

Infrared presence detection. Shower starts when hand is at 4cm from the sensor

Shuts off on demand or automatically after ~60 seconds.

Duty flush (~60 seconds every 24 hours after the last use).

Flow rate set at 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.

Concealed fixings.

Filter.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC shower panel - Ref. 452300

Supply	6V battery
Connector	M1/2"
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Finish	Aluminium
Norms	ACS 🗓 🔘
Warranty	30 WARRANTY

