

SECURITHERM dual control shower panel

Ref. 792344

Thermostatic and mechanical dual control

2024 UK public price excluding VAT: £1,148.95




DESCRIPTION

SECURITHERM dual control shower panel - Ref. 792344

Dual control thermostatic shower panel with handset:
Large model satin stainless steel shower panel for wall-mounted, exposed installation.
Top inlet via in-line stopcocks M½".
SECURITHERM thermostatic shower mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.
Handset with removable flexible via rapid push-fit STOP connector, wall support supplied.
Non-time flow valves control fixed ROUND shower head and handset with flexible.
Thermal shocks are possible.
Concealed fixings.
Filters and non-return valves.
Shower panel suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM dual control shower panel - Ref. 792344

Connector	M½"
Technology	Non-time flow
Height	1,220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS  
Warranty	



ADVANTAGES



Thermostatic temperature regulation



Instant shut-off if cold water fails



Fixed shower head or handset



Aluminium panel, brass controls

