

# SECURITHERM Securitouch thermostatic shower mixer

Ref. H9769S

Thermostatic mixer with no non-return valves

2024 UK public price excluding VAT: £285.00



## DESCRIPTION

**SECURITHERM Securitouch thermostatic shower mixer - Ref. H9769S**

SECURITHERM dual control thermostatic shower mixer.  
Thermostatic mixer with no non-return valves on the inlets (reduced bacterial proliferation).

No risk of cross flow between hot and cold water.

Mixer with anti-scalding failsafe: shuts off automatically if cold supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails.

Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic cartridge for temperature adjustment.

¼-turn ceramic head for flow rate adjustment.

Temperature control up to 43°C.

Double temperature limiter: 1st limiter set at 41°C, 2nd limiter set at 43°C.

Thermal shocks are possible without removing the control knob or shutting off the cold water supply.

Flow rate limited to 9 lpm at 3 bar.

Ergonomic controls.

M½" shower outlet.

F¾" inlets with integrated filters.

Mixer supplied with offset standard wall connectors M½" M¾".





Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Shower mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM Securitouch thermostatic shower mixer - Ref. H9769S**

Connector	M1/2"
Technology	SECURITHERM Securitouch thermostatic mixer, no-non-return valves
Depth	84 mm
Length	260mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS   
Warranty	

## ADVANTAGES



SECURITHERM: Anti-scalding safety



Maximum hygiene: no non-return  
valves



Securitouch thermal insulation  
prevents burns



Thermostatic: total temperature  
stability

