

Securitouch thermostatic shower kit

Ref. H964115

Thermostatic sequential mixer with no non-return valves

2024 UK public price excluding VAT: £651.51



DESCRIPTION

Securitouch thermostatic shower kit - Ref. H964115

Shower kit for exposed wall mounting:

- SECURITHERM thermostatic sequential shower mixer (ref. H9640). Thermostatic sequential mixer: opens and closes with cold water. Mixer with no non-return valves on the inlets (reduces bacterial proliferation). No risk of cross flow between the hot and cold water. Sequential mixer with anti-scalding failsafe: shuts off automatically if cold or hot water supply fails. Securitouch thermal insulation prevents burns. Scale-resistant thermostatic sequential cartridge for adjusting the flow rate and the temperature. Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C. Thermal shocks are possible. Body with smooth interior and low water volume (reduces niches where bacteria can develop). Chrome-plated brass body and Hygiene lever L.100mm. M3/4" shower outlet, top outlet. Wall-mounted mixer with inline STOP/CHECK connectors, M1/2" M3/4". Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics. Suitable for people with reduced mobility.
 - Fixed TONIC JET shower head with automatic flow rate regulation. Flow rate 6 lpm at 3 bar. Ligature-resistant, scale-resistant spray head with adjustable nozzle. Drains systematically after use: no water or impurity retention. Chrome-plated solid brass body fixed in place with concealed locking screws.
 - Ø 16mm shower column with reinforced collar (fixing plate and screws included).
- 30-year warranty.

TECHNICAL CHARACTERISTICS

Securitouch thermostatic shower kit - Ref. H964115

| | |
|---------------------|---|
| Technology | Thermostatic single control SECURITHERM, Securitouch |
| Flow rate | 6 lpm |
| Temperature limiter | 39°C |
| Finish | Chrome-plated brass |
| Warranty |  |

ADVANTAGES

-  Sequential: opens/closes with cold water
-  Maximum hygiene: no non-return valves
-  SECURITHERM: optimal anti-scalding safety
-  Thermostatic: complete temperature stability

