BINOPTIC electronic tap

Ref. 49801515

Battery-operated, Ø 15mm conical inlets

2024 UK public price excluding VAT: £590.05



DESCRIPTION

BINOPTIC electronic tap - Ref. 49801515

Deck-mounted electronic basin tap:

Independent IP65 electronic control unit.

Battery-operated with 123 6V Lithium batteries.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated brass body.

PEX flexible with filter and solenoid valve Ø 15mm.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces bacterial development).

Drop height: 250mm for countertop washbasins.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



90% water savings



Total hygiene: no manual contact



Anti-bacterial proliferation duty flush




Sleek design

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 49801515

Supply	6V batteries
Connector	M1/2" Ø 15
Technology	Electronic
Drop height	250mm
Spout length	185mm
Flow rate	3 lpm
Norms	WRAS
Warranty	30 S



© DELABIE https://www.delabie.co.uk