DELABIE

BIOFIL 2 month shower filter

Ref. 20261

Sterile

units.

2024 UK public price excluding VAT: £95.25

r Image: Constant of the second s

BIOFIL anti-Legionella and all-germ shower head filter. Device material: ABS Type of membrane: tubular microfiltration. Membrane made from polyethylene. Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade. Qualified water volume per duration of use: 6,000 litres. Filtration flow rate: 6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap). Maximum upstream pressure at the point-of-use: 5 bar. Maximum lifespan: 2 months after installation. Resistance to thermal shocks: 70°C for 30 minutes. Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total). Sterile filter. Individually wrapped, sterile. CE Class Is medical device. Weight: empty filter 105g / full filter 186g. Single reference. Must be ordered in quantities of 10. Packaged in boxes of 10

TECHNICAL CHARACTERISTICS

BIOFIL 2 month shower filter		Ref.	20261
------------------------------	--	------	-------

Connector	M1/2"
Technology	Filtration terminale
Height	62mm
Flow rate	6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar
Diameter	56mm
Lifespan	2 months
Norms	ACS WRAS BWGL CE



