

# Recessed thermostatic sequential shower mixer

Ref. H9631

SECURITHERM mixer with no non-return valves, kit 2/2

2024 UK public price excluding VAT: £303.71







## DESCRIPTION

Recessed thermostatic sequential shower mixer - Ref. H9631



Recessed thermostatic shower mixer, kit 2/2 :  
Thermostatic sequential shower mixer: opens/closes with cold water.  
Mixer with no non-return valves on the inlets (reduces bacterial development).  
No risk of cross flow between the hot and cold water.  
Sequential mixer with anti-scalding failsafe: shuts off immediately if cold water supply fails.  
Prevents cold showers: shuts off immediately if hot water supply fails.  
Securitouch thermal insulation prevents burns.  
Scale-resistant thermostatic sequential cartridge for adjusting flow rate and temperature.  
Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.  
Thermal shocks are possible.  
Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head.  
ERGO controls.  
M $\frac{3}{4}$ " inlets with integrated filters.  
Order a wall-mounted outlet or shower head to complete.  
Bright polished stainless steel cover plate 166 x 166mm.  
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
Sequential mixer ideal for people with reduced mobility.  
Shower mixer with 30-year warranty.  
Order with waterproof recessing housing ref. H96BOX.

## ADVANTAGES

-  Sequential: opens/closes with cold water
-  Maximum hygiene: no non-return valves
-  SECURITHERM: optimal anti-scalding safety
-  Thermostatic: total temperature stability

## TECHNICAL CHARACTERISTICS

Recessed thermostatic sequential shower mixer - Ref. H9631

Technology	SECURITHERM Securitouch thermostatic sequential shower mixer
Flow rate	Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS 
Warranty	
Repairability	