BINOPTIC 2 electronic tap

Ref. 375106

Batteries, deck-mounted, H. 250mm

2024 UK public price excluding VAT: £0.00



DESCRIPTION

BINOPTIC 2 electronic tap - Ref. 375106

Deck-mounted satin electronic basin tap:

Operated by CR123 Lithium 6V batteries.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant aerator.

Adjustable duty flush (~60 seconds every 24 hours after the last use).

Stainless steel tap, 250mm high for countertop basins.

Sensor at the end of the spout optimises presence detection.

PEX flexible with filter.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Smooth interior spout with low water volume (limits bacterial niches).

Set presence detection range, duty flush and launch thermal shocks manually. Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Anti-bacterial proliferation duty flush




Sleek design

TECHNICAL CHARACTERISTICS

BINOPTIC 2 electronic tap - Ref. 375106

Supply	6V batteries
Connector	M3/8"
Technology	Electronic
Drop height	250mm
Flow rate	3 lpm
Finish	Satin
Warranty	30 g



© DELABIE https://www.delabie.co.uk