BIOFIL 4-month shower head filter

Ref. 20461

Sterile

2024 UK public price excluding VAT: £116.63



ADVANTAGES



Anti-Legionella and all-germ



Space saving



Optimised positioning: tilting connector



Lifespan: 4 months after installation

DESCRIPTION

BIOFIL 4-month shower head filter - Ref. 20461

DELABIE anti-Legionella and all-germ shower filter.

Device made from ABS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: $0.1\mu m$ nominal and $0.2\mu m$ absolute sterilising grade.

Qualified water volume per duration of use: 12,000 litres.

Filtration flow rate: 6.5 lpm at 1 bar, 11.8 lpm at 3 bar and 14.1 lpm at 5 bar

(filter only, excludes any flow rate restriction in the tap).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 4 months after installation.

Resistance to thermal shocks: 70°C for 30 minutes.

Resistance to chemical shocks: active chlorine levels up to 100 ppm for 4 hours (cumulative total).

Sterile filter.

Weight: empty filter 133g / full filter 259g.

Packaged in boxes of 10 units.

TECHNICAL CHARACTERISTICS

BIOFIL 4-month shower head filter - Ref. 20461

Connector	M1/2"
Technology	Point-of-use filtration
Height	77mm
Length	194mm
Flow rate	6.5 lpm at 1 bar, 11.8 lpm at 3 bar and 14.1 at 5 bar
Diameter	56mm
Lifespan	4 months
Norms	ACS WRAS KTW CE

