Mechanical mixer with retracting hand spray

Ref. 2211L

Single hole mechanical mixer with retracting hand spray



Mechanical mixer with retracting hand spray - Ref. 2211L

Deck-mounted mechanical sink mixer suitable for baby baths.

Single hole mixer with retracting hand spray with swivelling spout H. 105 mm L. 200 mm.

Ø 40mm standard ceramic cartridge with pre-set maximum temperature limiter.

Securitouch thermal insulation prevents burns.

Mechanical mixer with retracting hand spray with 2 jet options: flow straightener/rain effect.

Body with smooth interior.

Flow rate limited to 7 lpm at 3 bar.

Chrome-plated brass body and Hygiene control lever L. 175mm.

BIOSAFE flexible shower hose reduces bacterial proliferation: transparent polyurethane flexible hose ensures replacement if biofilm is present, smooth interior and exterior.

Narrow flexible (interior Ø 6mm), low water volume.

Specific counterweight.

PEX flexibles F%".

Fixing reinforced by 2 stainless steel rods.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

FO /OII

Single hole mixer suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical mixer with retracting hand spray - Ref. 2211L

| Connector | F3/8" |
|---------------------|---------------------|
| Drop height | 105mm |
| Spout length | 200mm |
| Flow rate | 7 lpm at 3 bar |
| Temperature limiter | Yes |
| Finish | Chrome-plated brass |
| Norms | ACS (S) |
| | |
| Warranty | 30 ∰ WARRANTY |



ADVANTAGES



Hygiene: transparent flexible with smooth interior



Hygiene lever: no manual contact



Comfort: retracting hand spray with 2 jet options



Securitouch: thermal insulation prevents burns

