Mechanical basin mixer

Ref. 2720T

Single hole mechanical mixer H. 95mm L. 120mm



DESCRIPTION

Mechanical basin mixer - Ref. 2720T

Deck-mounted mechanical basin mixer.
Single hole mixer with a curved spout H. 95mm L. 120mm fitted with a hygienic BIOSAFE outlet.
Spout suitable for fitting a BIOFIL point-of-use filter.
Ø 35mm ceramic cartridge with a pre-set maximum temperature limiter.
Body and spout with smooth interior (reduced bacterial development).
No risk of cross flow between the hot and cold water.
No non-return valves on the inlets.
Flow rate regulated at 5 lpm.
Solid control lever.
Ergonomic, stainless steel pop-up waste 1 1/4".
F3/8" PEX flexibles.
Fixing reinforced via 2 stainless steel rods.
Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Single hole mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.
Also available with copper tails.

ADVANTAGES

- Hygiene: smooth interior reduces bacteria
- Maximum hygiene: low water volume
- Thermal shocks are possible without removing lever
- Ergonomic: solid lever is easy to grip

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2720T

Connector	F3/8"
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated stainless steel
Norms	ACS, WRAS, NF
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

