Mechanical basin mixer

Ref. 2720L

Single hole mechanical mixer H. 95mm L. 120mm

DESCRIPTION

Mechanical basin mixer - Ref. 2720L

Deck-mounted mechanical basin mixer.
Single hole mixer with curved spout H. 95mm L. 120mm fitted with a hygienic BIOSAFE outlet.
Spout suitable for fitting a BIOFIL point-of-use filter.
Ø 35mm ceramic cartridge with a pre-set maximum temperature limiter.
Body and spout with smooth interior (reduced bacterial development).
Thermal shocks are easy to undertake without removing the control lever or shutting off the water supply.
Flow rate limited to 5 lpm.
Hygiene control lever L. 150mm.
Ergonomic, brass pop-up waste 1 1/4".
F3/8" PEX flexibles.
Fixing reinforced via 2 stainless steel rods.
Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Mixer with 30-year warranty.
Also available with copper tails.

ADVANTAGES

- Hygiene: smooth interior reduces bacteria
- Hygiene: low water volume
- Thermal shocks are possible without removing lever
- Hygiene lever: mixer requires no manual contact

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2720L

Connector	F3/8"
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS WRAS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY