## Mechanical basin mixer

Ref. 2720L

Single hole mechanical mixer H. 95mm L. 120mm



## **ADVANTAGES**



Hygiene: smooth interior reduces bacteria



Hygiene: low water volume



Thermal shocks are possible without removing lever



Hygiene lever: mixer requires no manual contact



BIOSAFE outlet. Spout suitable for fitting a BIOFIL point-of-use filter.

Ø 35mm ceramic cartridge with a pre-set maximum temperature limiter.

Body and spout with smooth interior (reduced bacterial development).

Thermal shocks are easy to undertake without removing the control lever or shutting off the water supply.

Single hole mixer with curved spout H. 95mm L. 120mm fitted with a hygienic

Flow rate limited to 5 lpm.

**DESCRIPTION** 

Hygiene control lever L. 150mm.

Ergonomic, brass pop-up waste 1 1/4".

Mechanical basin mixer - Ref. 2720L

Deck-mounted mechanical basin mixer.

F3/8" PEX flexibles.

Fixing reinforced via 2 stainless steel rods.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer with 30-year warranty.

Also available with copper tails.

## TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2720L

| Connector           | F3/8"                               |
|---------------------|-------------------------------------|
| Drop height         | 95mm                                |
| Spout length        | 120mm                               |
| Flow rate           | 5 lpm                               |
| Temperature limiter | Yes                                 |
|                     |                                     |
| Finish              | Chrome-plated brass                 |
| Norms               | Chrome-plated brass  ACS WRAS UVERS |
|                     |                                     |

