

Mechanical basin mixer

Ref. 2720L

Single hole mechanical mixer H. 95mm L. 120mm

DESCRIPTION

Mechanical basin mixer - Ref. 2720L

Deck-mounted mechanical basin mixer.
Single hole mixer with curved spout H. 95mm L. 120mm fitted with a hygienic BIOSAFE outlet.
Spout suitable for fitting a BIOFIL point-of-use filter.
Ø 35mm ceramic cartridge with a pre-set maximum temperature limiter.
Body and spout with smooth interior (reduced bacterial development).
No risk of cross flow between the hot and cold water.
No non-return valves on the inlets.
Thermal shocks are easy to undertake without removing the control lever or shutting off the water supply.
Flow rate regulated at 5 lpm.
Hygiene control lever L. 150mm.
Ergonomic, stainless steel pop-up waste 1 1/4".
F3/8" PEX flexibles.
Fixing reinforced via 2 stainless steel rods.
Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Mixer with 30-year warranty.
Also available with copper tails.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2720L

Connector	F3/8"
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated stainless steel

Norms	   
Warranty	
Repairability	



ADVANTAGES



Hygiene: smooth interior reduces bacteria



Hygiene: low water volume



Thermal shocks are possible without removing lever



Hygiene lever: mixer requires no manual contact

