

Mechanical basin mixer

Ref. 2721L

Single hole mechanical mixer H. 95mm L. 120mm



DESCRIPTION

Mechanical basin mixer - Ref. 2721L

Deck-mounted mechanical basin mixer.
Single hole mixer with a curved spout H. 95mm L. 120mm fitted with hygienic flow straightener.
Spout suitable for fitting a BIOFIL point-of-use filter.
Ø 35mm ceramic cartridge with pre-set maximum temperature limiter.
Body and spout with smooth interiors (reduces bacterial development).
Thermal shocks are easy to undertake without removing the lever or shutting off the water supply.
Flow rate regulated at 5 lpm.
Hygiene control lever L. 150mm.
Without pop-up waste.
F3/8" PEX flexibles.
Fixing reinforced via 2 stainless steel rods.
Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Single hole mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.
Also available with copper tails.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2721L

Connector	F3/8"
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS NF WRAS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

ADVANTAGES



Hygiene: smooth interior reduces bacteria



Maximum hygiene: low water volume



Thermal shock without removing the control lever



Hygiene lever: mixer requires no manual contact

