

BIOCLIP mechanical basin mixer

Ref. 2821T

Single hole mechanical removable mixer H. 95mm L. 120mm, solid lever

DESCRIPTION

BIOCLIP mechanical basin mixer - Ref. 2821T

Deck-mounted mechanical basin mixer.
 BIOCLIP mechanical mixer: mixer can be removed entirely for cleaning and disinfection.
 Single hole mixer with spout H. 95mm L. 120mm fitted with a BIOSAFE hygienic flow straightener.
 Spout suitable for fitting a BIOFIL point-of-use filter.
 Ø 35mm ceramic cartridge with pre-set maximum temperature limiter.
 Thermal shocks are possible without removing the control lever or shutting off the cold water supply.
 Body and spout with smooth interiors and low water volume.
 No risk of cross flow between the hot and cold water.
 No non-return valves on the inlets.
 Flow rate regulated at 5 lpm at 3 bar.
 Solid control lever.
 Without pop-up waste.
 PEX flexibles F3/8" supplied with stopcocks in chrome-plated brass.
 Fixing reinforced via 2 stainless steel rods.
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Single hole mixer suitable for people with reduced mobility.
 Mixer with 30-year warranty.
 Also available with copper tubes.

TECHNICAL CHARACTERISTICS

BIOCLIP mechanical basin mixer - Ref. 2821T

Connector	F3/8"
Technology	BIOCLIP removable mixer
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   
Warranty	



ADVANTAGES



Hygiene: remove for internal cleaning




Hygiene: smooth interior reduces bacteria



Pre-set maximum temperature limiter



Ergonomic: solid lever is easy to grip



Repairability

