Mechanical basin mixer

Ref. 2522

Single hole mechanical mixer with swivelling spout H. 100mm L. 170mm



ADVANTAGES



Hygiene: smooth interior reduces bacteria



Pre-set maximum temperature limiter



Ergonomic: sculptured lever is easy to grip



User comfort: swivelling spout

DESCRIPTION

Mechanical basin mixer - Ref. 2522

Deck-mounted mechanical basin mixer.

Single hole mechanical mixer with swivelling spout H. 100mm L. 170mm with hygienic flow straightener.

Spout suitable for fitting a BIOFIL point-of-use filter.

Ø 40mm classic ceramic cartridge with pre-set maximum temperature limiter. Body and spout with smooth interiors.

Flow rate limited to 5 lpm at 3 bar.

Sculptured control lever.

PEX flexibles F3/8".

Fixing reinforced by 2 stainless steel rods.

Mechanical mixer ideal for use in healthcare facilities, retirement and care homes, hospitals and clinics.


Single hole mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical basin mixer - Ref. 2522

Connector	F3/8"
Height	143mm
Drop height	100mm
Spout length	170mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS OF CO
Warranty	30 gg WASSANTY
Repairability	50° germanuty



© DELABIE https://www.delabie.co.uk