

# SECURITHERM EP pressure-balancing basin mixer

Ref. 2520EP

Single hole mechanical mixer H. 85mm, L. 135mm

## DESCRIPTION

**SECURITHERM EP pressure-balancing basin mixer - Ref. 2520EP**

Deck-mounted mechanical basin mixer with pressure-balancing. Single hole mixer with spout H. 85mm L. 135mm with BIOSAFE hygienic spout outlet.

Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if cold water supply fails (and vice versa).

Stable temperature regardless of pressure and flow rate variations in the system.

Flow rate limited to 5 lpm at 3 bar.

Sculptured control lever.

Ergonomic, brass pop-up waste 1 1/4".

PEX flexibles F3/8" with filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM EP pressure-balancing basin mixer - Ref. 2520EP**

|                     |                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector           | F3/8"                                                                                                                                                                                                                                                                                                                                           |
| Technology          | SECURITHERM EP mechanical mixer                                                                                                                                                                                                                                                                                                                 |
| Height              | 165mm                                                                                                                                                                                                                                                                                                                                           |
| Drop height         | 85mm                                                                                                                                                                                                                                                                                                                                            |
| Spout length        | 135mm                                                                                                                                                                                                                                                                                                                                           |
| Flow rate           | 5 lpm at 3 bar                                                                                                                                                                                                                                                                                                                                  |
| Temperature limiter | Yes                                                                                                                                                                                                                                                                                                                                             |
| Finish              | Chrome-plated stainless steel                                                                                                                                                                                                                                                                                                                   |
| Norms               |     |
| Warranty            |                                                                                                                                                                                                                                                              |
| Repairability       |                                                                                                                                                                                                                                                              |



## ADVANTAGES



HW flow rate reduced if CW fails



EP: reduces temperature variations



Hygiene: BIOSAFE hygienic outlet with no grid



Ergonomic sculptured control lever is easy to grip

