

# Mechanical basin mixer

Ref. 2506T1

Single hole mechanical mixer with swivelling spout H. 195mm L. 150mm



## DESCRIPTION

**Mechanical basin mixer - Ref. 2506T1**

Deck-mounted mechanical basin mixer.  
Single hole mechanical mixer with swivelling spout H. 195mm L. 150mm fitted with a BIOSAFE hygienic outlet.  
Ø 35mm ceramic cartridge with maximum temperature limiter supplied but not installed.  
Spout with smooth interior.  
No risk of cross flow between the hot and cold water.  
No non-return valves on the inlets.  
Flow rate limited to 5 lpm at 3 bar.  
Slimline control lever.  
Stainless steel pop-up waste 1 1/4".  
F3/8" PEX flexibles.  
Fixing reinforced by 2 stainless steel rods.  
Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
Single hole mixer suitable for people with reduced mobility.  
Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**Mechanical basin mixer - Ref. 2506T1**

|               |                                                                                                                                                                                                                                                             |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector     | F3/8"                                                                                                                                                                                                                                                       |
| Drop height   | 195mm                                                                                                                                                                                                                                                       |
| Spout length  | 150mm                                                                                                                                                                                                                                                       |
| Flow rate     | 5 lpm at 3 bar                                                                                                                                                                                                                                              |
| Finish        | Chrome-plated stainless steel                                                                                                                                                                                                                               |
| Norms         |    |
| Warranty      |                                                                                                                                                                          |
| Repairability |                                                                                                                                                                          |

## ADVANTAGES



Hygiene: smooth interior reduces bacteria



Hygiene: BIOSAFE hygienic outlet with no grid



Ergonomic: slimline lever is easy to grip



Comfort: optimised height and spout projection

