Mechanical mixer for sinks or troughs

Ref. 2565T3

Single hole, single control tall mixer with ceramic cartridge



DESCRIPTION

Mechanical mixer for sinks or troughs - Ref. 2565T3

Deck-mounted tall mechanical sink mixer.
Single hole, single control mixer with fixed spout H. 305mm L. 140mm.
Tall mixer with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.
Ø 35mm classic ceramic cartridge with pre-set maximum temperature limiter.
Body and spout with smooth interiors (reduced bacterial development).
No risk of cross flow between the hot and cold water.
No non-return valves on the inlets.
Thermal shocks are easy to undertake without removing control lever or shutting off the cold water.
Flow rate limited to 9 lpm at 3 bar.
Chrome-plated brass body and base.
Hygiene control lever L. 185mm requires no manual contact.
PEX flexibles F3/8".
Reinforced fixings by 2 stainless steel rods.
Mechanical mixer ideal for healthcare facilities, retirement or care homes, hospitals and clinics.
Single hole mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.

ADVANTAGES

- Hygiene: smooth interior reduces bacteria
- Thermal shock without removing the control lever
- Pre-set maximum temperature limiter
- No manual contact thanks to Hygiene control lever

TECHNICAL CHARACTERISTICS

Mechanical mixer for sinks or troughs - Ref. 2565T3

Connector	F3/8"
Height	431mm
Drop height	305mm
Spout length	140mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS, WRAS
Warranty	30 YEARS WARRANTY
Repairability	50 YEARS REPAIRABILITY

