

SECURITHERM thermostatic shower mixer

Ref. H9739

Dual control thermostatic shower mixer



DESCRIPTION

SECURITHERM thermostatic shower mixer - Ref. H9739

SECURITHERM dual control thermostatic shower mixer:
Mixer with anti-scalding safety: shuts off automatically if cold water supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails.

Scale-resistant thermostatic cartridge for temperature adjustment.

1/4-turn ceramic head for flow rate adjustment.

Temperature control from 25 - 40°C with maximum temperature limiter set at 38°C.

Thermal shocks are possible without removing the control knob or shutting off the cold water.

Flow rate regulated at 9 lpm.

Chrome-plated brass body and CLASSIC controls.

M1/2" shower outlet.

Filters and non-return valves F3/4" integrated on the inlets.

Mixer with offset STOP/CHECK wall connectors, M1/2" M3/4".

Ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Shower mixer with 30-year warranty.

ADVANTAGES



SECURITHERM: Optimum anti-scalding safety



Pre-set maximum temperature limiter



Thermostatic: total temperature stability



Ergonomic: controls are easy to grip

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic shower mixer - Ref. H9739

Connector	M1/2"
Technology	SECURITHERM thermostatic dual control mixer
Length	81mm
Width	280mm
Flow rate	9 lpm
Temperature limiter	38°C
Finish	Chrome-plated brass
Norms	   
Warranty	

