

# Auto-draining shower kit with mechanical mixer

Ref. 2739SHYG

Shower kit with wall-mounted single control mixer

## DESCRIPTION

**Auto-draining shower kit with mechanical mixer - Ref. 2739SHYG**

Shower kit with wall-mounted single control mechanical mixer.  
Shower kit with auto-draining device.

- Wall-mounted single control mixer with Securitouch thermal insulation to prevent burns.
  - Ø 40mm classic ceramic cartridge with pre-set maximum temperature limiter. Body with smooth interior and low water volume.
  - Flow rate regulated at 9 lpm.
  - Chrome-plated brass body and sculptured control lever.
  - M1/2" shower outlet with integrated non-return valve.
  - Mixer with offset standard wall connectors, M1/2" M3/4".
  - Chrome-plated shower head (ref. 813) with flexible shower hose (836T3) and chrome-plated, adjustable, wall-mounted support (ref. 845).
  - Auto-draining device FM1/2" for installation between the flexible hose and the shower head automatically drains the shower head and flexible hose (ref. 880).
- Mixer is ideal for healthcare facilities, retirement homes, hospitals and clinics.  
Mixer suitable for people with reduced mobility.  
Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**Auto-draining shower kit with mechanical mixer - Ref. 2739SHYG**

|                     |                                                                                                |
|---------------------|------------------------------------------------------------------------------------------------|
| Connector           | M1/2"                                                                                          |
| Technology          | Securitouch shower mixer                                                                       |
| Depth               | 157mm                                                                                          |
| Width               | 182mm                                                                                          |
| Flow rate           | 9 lpm                                                                                          |
| Temperature limiter | Yes                                                                                            |
| Finish              | Chrome-plated brass                                                                            |
| Norms               | <b>ACS</b>  |
| Warranty            |             |
| Repairability       |             |



## ADVANTAGES



Hygiene: smooth interior reduces bacteria



Securitouch thermal insulation prevents burns



Maximum hygiene: low water volume.



Ergonomic: sculptured lever is easy to grip

