

# Single hole mixer - 100 lpm

Ref. 5610

Mixer with high flow rate with spout H. 315 L.300

## DESCRIPTION

Single hole mixer - 100 lpm - Ref. 5610

Single hole mixer for professional catering.  
Mixer for plunge sinks with swivelling, tubular spout H. 315mm L. 300mm.  
Star-shaped, brass flow straightener with smooth interior.  
Water-free guided valve heads with reinforced mechanisms.  
Shock-resistant, ergonomic ball levers.  
Flow rate 100 lpm at 3 bar suitable for plunge sinks.  
Full flow rate within half a turn.  
Chrome-plated brass body and spout.  
Soldered copper pipe water inlets.  
Single hole mixer with reinforced fixings.  
Mixer suitable for intensive use in professional kitchens.  
Mixer for commercial kitchens with 30-year warranty.

## TECHNICAL CHARACTERISTICS

Single hole mixer - 100 lpm - Ref. 5610

|               |                                                                                                                                                                                                                                                             |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Height        | 385mm                                                                                                                                                                                                                                                       |
| Drop height   | 315mm                                                                                                                                                                                                                                                       |
| Spout length  | 300mm                                                                                                                                                                                                                                                       |
| Flow rate     | 100 lpm                                                                                                                                                                                                                                                     |
| Finish        | Chrome-plated brass                                                                                                                                                                                                                                         |
| Norms         |    |
| Warranty      |                                                                                                                                                                          |
| Repairability |                                                                                                                                                                          |



## ADVANTAGES



Rapid fill: flow rate 100 lpm at 3 bar



Shock-resistant control levers for intensive use



Brass body and spout suitable for intensive use



Maximum hygiene: spout with smooth interior

