

## BINOPTIC electronic tap

Ref. 378015

Mains supply

### DESCRIPTION

**BINOPTIC electronic tap - Ref. 378015**

Deck-mounted electronic basin tap:  
Independent IP65 electronic control unit.  
230/12V mains supply with transformer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24hr after last use).  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Chrome-plated brass body.  
PEX flexible with filter and solenoid valve M3/8".  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).  
Suitable for people with reduced mobility.  
30-year warranty.

### TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 378015**

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply        | 230/12V mains supply                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Connector     | M3/8"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Technology    | Electronic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Drop height   | 90mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Spout length  | 125mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Flow rate     | 3 lpm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Norms         |    <br>   |
| Warranty      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Repairability |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |



### ADVANTAGES

-  90% water savings
-  Hygiene: no manual contact
-  Independent IP65 electronic control unit
-  Anti-bacterial proliferation duty flush

