

# BINOPTIC electronic tap

Ref. 379DER

Mains supply



## DESCRIPTION

**BINOPTIC electronic tap - Ref. 379DER**

Electronic basin tap for cross wall installation.  
Independent IP65 electronic control unit.  
230/12V mains supply with transformer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Sensor at the end of the spout optimises presence detection.  
Filters and solenoid valves M3/8".  
Chrome-plated brass body.  
Chrome-plated spout L. 205mm for cross wall installation ≤ 190mm.  
Cable for sensor L. 120mm, flexibles and mounting all pass through the same hole.  
Anti-blocking security.  
Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC electronic tap - Ref. 379DER**

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply        | 230/12V mains supply                                                                                                                                                                                                                                                                                                                                                                                                                |
| Connector     | M3/8"                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Technology    | Electronic                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Spout length  | 205mm                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Flow rate     | 3 lpm                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Norms         |      |
| Warranty      |                                                                                                                                                                                                                                                                                                                                                  |
| Repairability |                                                                                                                                                                                                                                                                                                                                                  |

## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Independent IP65 electronic control unit



LED diagnostic aid

