

## TEMPOMIX time flow mixer

Ref. 79500015

With stopcocks





### DESCRIPTION

TEMPOMIX time flow mixer - Ref. 79500015





Deck-mounted single control time flow basin mixer:  
 Soft-touch operation.  
 Temperature control and operation via the push-button.  
 Time flow ~7 seconds.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm.  
 Scale-resistant flow straightener.  
 Chrome-plated solid brass body.  
 PEX flexibles Ø 15mm for compression fittings with stopcocks, filters and non-return valves.  
 Fixing reinforced by 2 stainless steel rods.  
 Adjustable maximum temperature limiter.  
 Ergonomic chrome-plated metal push-button.  
 10-year warranty.  
 \*Add CR to the end of the reference (79500015CR) to order with copper tails.

### TECHNICAL CHARACTERISTICS

TEMPOMIX time flow mixer - Ref. 79500015

Connector	M1/2" Ø 15mm
Technology	Time flow
Drop height	60mm
Spout length	110mm
Flow rate	3 lpm
Norms	
Warranty	

### ADVANTAGES

-  Soft-touch operation
-  85% water savings
-  Chrome-plated solid brass, reinforced fixings
-  Temperature control

