TEMPOMATIC electronic shower valve

Ref. 452565

Electronic



DESCRIPTION

TEMPOMATIC electronic shower valve - Ref. 452565

Recessed electronic shower valve:

TEMPOMATIC electronic valve for mixed water supply.

Recessed installation.

Power supply by electronic unit with solenoid valve $\frac{1}{2}$ ". 230/12V transformer.

2 operation modes:

- Automatic activation via presence detection.
- Voluntary ON/OFF activation by passing hand in front of sensor ~10 cm.

Duty flush (~60 seconds every 24 hours after the last use).

Adjustable time flow from 30 to 60 seconds.

Flow rate 20 lpm.

Chrome-plated solid brass.

Electronic shower valve suitable for people with reduced mobility.

30-year warranty.

This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOMATIC electronic shower valve - Ref. 452565

Supply	230/12V mains supply
Connector	1/2"
Technology	Electronic
Flow rate	20 lpm
Norms	ACS (E
Warranty	30 g

ADVANTAGES



230/12 V




Total hygiene: no manual contact



Anti-bacterial duty flush



2 operation modes



© DELABIE https://www.delabie.co.uk