

TEMPOMIX time flow shower kit

Ref. 790909

Single control time flow



DESCRIPTION

TEMPOMIX time flow shower kit - Ref. 790909

Time flow shower kit with recessed waterproof housing:

Chrome-plated wall plate Ø 195mm.

Standard recessed housing.

Recessing depth can be adjusted from 28 to 43mm.

TEMPOMIX ¾" single control mixer.

Ligature-resistant collar.

Temperature control and operation via the push-button.

Maximum temperature limiter (can be adjusted by the installer).

Time flow ~30 seconds.

Flow rate 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.

M½" connectors for copper tubes Ø 14mm.

Integrated non-return valves and filters.

Chrome-plated metal push-button.

Suitable for people with reduced mobility.

30-year warranty.

Integrated non-return valves and filters. This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

ADVANTAGES



80% water savings



Wall recessed installation



Time flow system tested to over 500,000 operations



Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower kit - Ref. 790909

Connector	½"
Technology	Time flow
Flow rate	6 lpm
Norms	ACS  
Warranty	

