

TEMPOMIX time flow shower kit

Ref. 790909

Single control time flow



DESCRIPTION

TEMPOMIX time flow shower kit - Ref. 790909

Time flow shower kit with recessed waterproof housing:
 Chrome-plated wall plate Ø 195mm.
 Standard recessed housing.
 Recessing depth can be adjusted from 28 to 43mm.
 TEMPOMIX ¼" single control mixer.
 Ligature-resistant collar.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 M½" connectors for copper tubes Ø 14mm.
 Integrated non-return valves and filters.
 Chrome-plated metal push-button.
 Suitable for people with reduced mobility.
 30-year warranty.
 Integrated non-return valves and filters. This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower kit - Ref. 790909

Connector	½"
Technology	Time flow
Flow rate	6 lpm
Norms	  
Warranty	

ADVANTAGES



80% water savings



Wall recessed installation



Time flow system tested to over 500,000 operations



Soft-touch operation

