

TEMPOMIX time flow shower mixer

Ref. 790927

Single control time flow



DESCRIPTION

TEMPOMIX time flow shower mixer - Ref. 790927

Recessed time flow shower mixer:
 Chrome-plated metal wall plate Ø 195mm.
 Standard recessing housing.
 Recessing depth can be adjusted from 28 - 43mm.
 TEMPOMIX ¾" single control mixer.
 Ligature-resistant collar.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds.
 Flow rate 12 lpm at 3 bar.
 M½" connectors for Ø 14mm copper tubes.
 Chrome-plated metal control.
 Integrated non-return valves and filters.
 30-year warranty.
 This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

ADVANTAGES



Wall recessed installation








Time flow system tested to over 500,000 operations



Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower mixer - Ref. 790927

| | |
|------------|---|
| Connector | ½" |
| Technology | Time flow |
| Flow rate | 12 lpm |
| Norms |     |
| Warranty |  |

