

# ROUND shower head

Ref. 709010

Scale-resistant



## DESCRIPTION

**ROUND shower head - Ref. 709010**

Fixed shower head:  
For installation on panels from 1 - 15mm.  
Flow rate 6 lpm at 3 bar.  
Automatic flow rate regulation.  
Scale-resistant and ligature-resistant adjustable nozzle.  
Chrome-plated solid brass.  
Fixed with concealed blocking screw.  
Systematically drains after use (no water retention or impurity deposits).  
Inlets M $\frac{1}{2}$ ".  
30-year warranty.

## ADVANTAGES



Water savings up to 80%



Scale-resistant nozzle, no water retention



Adjustable conical jet



Chrome-plated brass, new ligature-resistant nozzle

## TECHNICAL CHARACTERISTICS

**ROUND shower head - Ref. 709010**

|           |                                                                                                                                                                                                                                                                                                                                                 |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector | $\frac{1}{2}$ "                                                                                                                                                                                                                                                                                                                                 |
| Depth     | 35mm                                                                                                                                                                                                                                                                                                                                            |
| Flow rate | 6 lpm                                                                                                                                                                                                                                                                                                                                           |
| Norms     |     |
| Warranty  |                                                                                                                                                                                                                                                              |

