

## PREMIX COMFORT

Ref. 731200

Group thermostatic mixing valve, mixed water 32°-42°C



### DESCRIPTION

**PREMIX COMFORT** - Ref. 731200

Group thermostatic mixing valve for mixed water from 32° to 42°C:

Anti-scalding safety.

Regulation of temperature variations.

Non-return valves and filters accessible from the exterior without having to remove the mechanism.

Thermal cartridge with no specific lever needed (push-button on the control knob).

Interchangeable cartridge with thermo-reactive cell.

High-resistance chrome-plated brass body.

Maximum hot water temperature: 85°C.

Differential hot water / mixed water: 15°C mini.

Pressure differences at the entrance: 1 bar maximum (0.5 bar recommended).

Minimum pressure / maximum: 1 to 10 bar (1 to 5 bar recommended).

Left hand side hot water inlet (red ring) and right hand side cold water inlet (blue ring).

Mixed water outlet at the top (purple ring).

For bottom outlet: unscrew / place lid at the top and outlet connector at the bottom.

Maximum temperature limiter, can be adjusted by the installer.

Reduced risk of scalding by limiting temperature at the point-of-use.

55 lpm - M<sup>3</sup>/<sub>4</sub>".

30-year warranty.

### ADVANTAGES



Automatic shut-off if cold water supply fails



Temperature stability



Accessible filters and non-return valves



Thermo-reactive cell

### TECHNICAL CHARACTERISTICS

**PREMIX COMFORT** - Ref. 731200

|               |                                                                                                                                                                                                                                                             |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector     | M <sup>3</sup> / <sub>4</sub> "                                                                                                                                                                                                                             |
| Technology    | Thermostatic                                                                                                                                                                                                                                                |
| Height        | 81mm                                                                                                                                                                                                                                                        |
| Depth         | 18mm                                                                                                                                                                                                                                                        |
| Length        | 120mm                                                                                                                                                                                                                                                       |
| Flow rate     | 55 lpm                                                                                                                                                                                                                                                      |
| Norms         |    |
| Warranty      |                                                                                                                                                                          |
| Repairability |                                                                                                                                                                          |

