# PREMIX COMPACT
# Thermostatic mixing valve

Ref. 733015

For mixed water 30 - 60°C

## DESCRIPTION

**PREMIX COMPACT Thermostatic mixing valve - Ref. 733015**

PREMIX COMPACT thermostatic mixing valve for mixed water distribution from 30 - 60°C:
For 1 to 11 points-of-use (depending on the flow rate).
Anti-scalding safety: immediate shut-off if cold or hot water supply fails.
Adjustable temperature from 30 - 60°C, can be blocked by the installer.
Brass body.
Filters and non-return valves.
Recommended flow rate range: from 5 - 33 lpm.
Thermal shocks are possible.
M½".
40mm centres.
30-year warranty.

## ADVANTAGES

- Automatic shut-off if cold water fails
- Temperature stability
- Accessible filters and non-return valves
- Thermo-reactive cell

## TECHNICAL CHARACTERISTICS

**PREMIX COMPACT Thermostatic mixing valve - Ref. 733015**

| | |
|---|---|
| Connector | M½" |
| Technology | Thermostatic |
| Length | 120mm |
| Finish | Nickel-plated |
| Norms | ACS, BELGAQUA, DVGW, kiwa |
| Warranty | 30 YEAR WARRANTY |
| Repairability | 50 YEARS REPAIRABILITY |