

TEMPOMATIC urinal valve

Ref. 428200

Electronic mains supply



DESCRIPTION

TEMPOMATIC urinal valve - Ref. 428200

Cross wall electronic urinal valve:

Mains supply, electronic control unit 12V with solenoid valve, filter and stopcock M $\frac{1}{2}$ ".

Cross wall installation for walls $\leq$ 225mm.

Shock-resistant infrared presence detector.

Detection distance, time flow and flow rate can be adjusted at installation.

Order the 230/12V transformer separately.

Presence detection delay is 3 seconds.

Automatic pre-rinse possible.

Time flow 3 sec. can be adjusted from 3 - 12 seconds.

Hygienic duty flush is possible every 24 hours after last use, prevents vacuums.

Flow rate 0.3 L/sec. at 3 bar pressure, can be adjusted.

Wall plate flush to the wall.

Threaded rods can be cut-to-size.

Compatible with rain water.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Total hygiene: no manual contact



ECO time flow 3 seconds



Cross wall installation



Hygienic duty flush

TECHNICAL CHARACTERISTICS

TEMPOMATIC urinal valve - Ref. 428200

Supply	Secteur 12V
Connector	1/2"
Technology	Electronic
Length	225mm
Flow rate	0.3 l/sec.
Norms	CE
Warranty	30 YEAR WARRANTY

