

# TEMPOMATIC direct flush valve

Ref. 463030

Direct flush WC valve



## DESCRIPTION

**TEMPOMATIC direct flush valve - Ref. 463030**

Flush system without cistern: directly connected to pipework.  
 Mains supply with 1" solenoid valve.  
 230/12V transformer.  
 IP65 independent electronic unit.  
 For cross wall installation on walls  $\leq 30$ mm.  
 Shock-resistant infrared presence detection sensor.  
 Contactless automatic flush when the user leaves or voluntary activation (when hand is detected  $\sim 4$ cm in front of the sensor).  
 Time flow  $\sim 7$  seconds, can be adjusted from 3 - 12 seconds.  
 Detection distance, flow rate and flush volume can be adjusted.  
 Stopcock FF1".  
 Vacuum breaker  $\varnothing 32$ mm  
 Connection washer  $\varnothing 32/55$ mm.  
 Wall plate flush to the wall.  
 Threaded rod can be cut to size.  
 Base flow rate: 1 L/sec at 1 bar dynamic pressure.  
 Compatible with rain water, sea water and gray water.  
 Suitable for rimless WC pans without flow rate regulation  
 Suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

**TEMPOMATIC direct flush valve - Ref. 463030**

|               |                                                                                                                                                                         |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply        | 230/12V mains supply                                                                                                                                                    |
| Connector     | 1"                                                                                                                                                                      |
| Technology    | Electronic                                                                                                                                                              |
| Length        | 30mm                                                                                                                                                                    |
| Norms         |   |
| Warranty      |                                                                                      |
| Repairability |                                                                                      |

## ADVANTAGES



Total hygiene: operate without manual contact



No cistern: no stagnant water



Voluntary or automatic flush



Cross wall installation

