TEMPOMATIC WC direct flush valve

Ref. 463150

Direct flush WC valve

DESCRIPTION

TEMPOMATIC WC direct flush valve - Ref. 463150

Flush system without cistern: directly connected to pipework.
Mains supply with 1" solenoid valve.
230/12V transformer.
IP65 independent electronic unit.
For installation on walls ≤ 160 mm.
Shock-resistant infrared presence detection sensor.
Voluntary activation (when hand is detected ~4cm in front of sensor) or automatic flush when user leaves.
Time flow ~7 seconds, can be adjusted from 3 - 12 seconds.
Detection distance, flow rate and flush volume can be adjusted.
Stopcock FF1".
Vacuum breaker Ø32mm.
Connection washer Ø 32/55mm.
Wall plate flush to the wall.
Base flow rate: 1 L/sec.
Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.
Threaded rod can be cut to size.
30-year warranty.

ADVANTAGES

- Total hygiene: operate without manual contact
- No cistern: no stagnant water
- Voluntary or automatic activation
- Cross wall installation

TECHNICAL CHARACTERISTICS

TEMPOMATIC WC direct flush valve - Ref. 463150

Supply	230/12V mains supply
Connector	1"
Technology	Electronic
Length	160mm
Norms	CE, BELGAQUA
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY