

# TEMPOFLUX 1 direct flush valve

Ref. 761627

Time flow direct flush WC valve



## DESCRIPTION

TEMPOFLUX 1 direct flush valve - Ref. 761627

Recessed time flow valve for direct flush:  
Stainless steel control plate 220 x 170mm.  
Multipurpose recessing housing.  
Soft-touch operation.  
Time flow ~7 seconds.  
Vacuum breaker.  
Integrated stopcock and flow/volume rate adjuster.  
Solid brass body and chrome-plated push-button.  
In-line inlet M $\frac{3}{4}$ ".  
Outlet connection for PVC tube Ø 26/32mm.  
Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).  
Base flow rate: 1 L/sec at 1 bar dynamic pressure.  
Compatible with rain water.  
Suitable for people with reduced mobility.  
30-year warranty.  
This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

## TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush valve - Ref. 761627

|           |                                                                                                                                                                         |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector | 3/4"                                                                                                                                                                    |
| Height    | 220mm                                                                                                                                                                   |
| Width     | 170mm                                                                                                                                                                   |
| Norms     |   |
| Warranty  |                                                                                      |

## ADVANTAGES



No cistern: no stagnant water



Wall recessed installation



Powerful flush and immediately available



Direct flush reduces the risk of leaks

